



MAUSER Open Head Steel Drums. The versatile one.

Made from steel plate. With UN approval for the save transport of dangerous liquids and solids of UN packaging group I, II and III.



MAUSER Open Head Steel Drums

For more than 100 years MAUSER has been developing its range of steel drums. By implementing the triple seam and the W-shaped bead the drop performance and strength of the drum

body was improved. The 216,5L open head steel drum developed by MAUSER is the international standard and is used in the chemical and oil industries.

Your Benefits

- Good space utilisation due to high stacking performance
- Removable lid eases the use of extraction systems or mixing devices
- Produced according to ISO 15750-1
- Optimal handling
- 100% drainable

Description

Steel plate according to ISO 3574 and ISO 16162 Material longitudinal seam welded, 2 rolling hoops, upper drum body **Body** crimped. Drum body and base connected with triple seam. Base Lid fully removable, gasket PUR foam or foam rubber. with outside located lever closure, options: **Clamping Ring** A) special profile, endings overlapping, liquid/solid approval B) normal profile, endings not overlapping, solid approval a) inside plain, outside spray painted Surfaces

b) inside with coating, outside spray painted

c) inside/outside galvanised

Blue, RAL 5010 Colour¹⁾

screen printing, body can be flat or with two or more rolling **Options**

hoops/beads, lid with closures G2" and G3/4"



Technical Data

Nominal Volume Outer Height			15,0 L 80,0 mm	Inner Diameter Outer Diameter	571,5 mm 585,0 mm	
Sheet Shell	Thickne: Base	ss [mm] Lid	Weight ²⁾ [kg]	Marking/UN Ap	proval	
A) Drums for dangerous liquids and solids, clamping ring with special profile ⁴⁾						
0,8	1,0	1,0	17,3	UN 1A2/Y/140	/ ³⁾ /D/BAM 9004-M1	UN 1A2/X417/S/ ³⁾ /D/BAM 9004-M1
0,9	1,0	1,0	18,4	UN 1A2/Y/140	/ ³⁾ /D/BAM 9004-M1	UN 1A2/X417/S/ ³⁾ /D/BAM 9004-M1
1,0	1,0	1,0	19,5	UN 1A2/Y/140	/ ³⁾ /D/BAM 9004-M1	UN 1A2/X417/S/ ³⁾ /D/BAM 9004-M1
1,2	1,2	1,2	23,0	UN 1A2/X1.5/18	30 / ³⁾ /D/BAM 9003-M1	UN 1A2/X423/S/ ³⁾ /D/BAM 9003-M1
B) Drums for dangerous solids, clamping ring with normal profile ⁵⁾						
0,8	1,0	1,0	16,3	-		UN 1A2/X250/S/ ³⁾ /D/BAM 10031-M1
0,9	1,0	1,0	17,4	-		UN 1A2/X250/S/ ³⁾ /D/BAM 10031-M1
1,0	1,0	1,0	18,5	-		UN 1A2/X250/S/ ³⁾ /D/BAM 10031-M1
1,2	1,2	1,2	22,0	-		UN 1A2/X285/S/ ³⁾ /D/BAM 10030-M1

¹⁾ Other colours and printing available 2) Weight and thickness tolerances according EN 10131 3) year of production 4) UN approved for the transport of dangerous liquids and solids 5) Un approved for the transport of dangerous solids

Quality Assurance



MAUSER is certified according to ISO 9001:2000. Our production is under external quality control according to BAM-GGR 001 within the "Überwachungsgemeinschaft Metall- und Fiberverpackungen e.V.".

Mauser Metallverpackungen GmbH

Schildgesstraße 71-163 • D-50321 Brühl • Germany Telefon: +49 (0)22 32 78-0 • Fax: +49 (0)22 32 78-1243

info@mausergroup.com www.mausergroup.com